



FAS
ANY PLACE. ANY BUSINESS.



900 | 1050

ADVANCED

FAS 900 – 1050 ADVANCED

- Drawer up to 8 (900 version) and 10 selections (1050 version);
- Straightforward, easy-to-clean design;
- Slide-in slide-out refrigerator unit with low consumption and quick replacement (patented). CO2 natural gas for maximum respect of the environment (GWP=1);
- Refrigeration with side ventilation to reduce consumption, minimise the effects of condensation and even out the internal temperatures of the dispenser (patented);
- Intelligent lighting with high-efficiency LEDs and energy-saving function;
- Manage, programme, update, clone and audit functions with standard USB pen drive or remotely via Fas Cloud+;
- Interactive user interface with 7" tablet;
- Drawer displays (depending on configuration);
- Riella lock;
- Easy Click system to configure the machine quickly and easily without technical tools;
- Typical possible configurations:
1T - 2T Snack + Drink + Food also with MULTITEMP reconfigurable sideboard and 3T;
- Insulation with polyurethane foam (HFC-free);
- Pre-cooling compartment;
- Product detection photocells;
- Full metal frame and drawers for solidity and durability.



Fas 900 Advanced

Fas 1050 Advanced



R744



R744
(Advanced 1T)



Easy click System

Pre cooling

General Features		Fas 900 Advanced	Fas 1050 Advanced
Dimensions	mm (H x L x P)	1830 x 900 x 790	1830 x 1050 x 790
Open door encumbrance	mm	1660	1810
Standard/max. number of drawers	nr.	6/7	6/7
Minimum internal temperature		+3°C with fridge safety on the bottom 3 drawers	
Power supply	V/Hz	230/50	230/50
Rated refrigerator power	W	450	450
Weight	Kg	224	239
Refrigeration system	Compact N-class compression - Evap. Ventilated - Cyclic defrosting		
Interface		Tablet 7"	Tablet 7"
Protocols	MDB/BDV/Executive		
Standard colour	Anodised extruded aluminium profile. Black surfaces - RAL 9005		



Fas International Spa
Via Lago di Vico, 60
36015 Schio · Vicenza · Italy
T +39 0445 502011

info@fas.it
www.fas.it

