



Fas
EXCELLENCE

1050

WWW.FAS.IT



Fas EXCELLENCE 1050

MAIN FEATURES

Enlarged capacity

Delivery bin and delivery door with enlarged dimensions to ensure the withdrawal of bulky products compared to the normal standard

7" Interface tablet

Interface enduser touchscreen customizable with logos, videos. Programming iconographic easy and fast.

Intelligent lighting

Power LED at high efficiency with programmable energy saving function; delivery bin illuminated intermittently when product is delivered

Fas Cloud +

Management, programming, updates, cloning and Audit functions on site or from remote via Fas Cloud+

Double Glazed glass with high efficiency

Laminated glass with security and low emission to avoid fogging and condensation

Typical Configurations available

Up to 3 different zone temperatures (Snack/Drink/Food); Lateral air flow to avoid build up condensation (patented)

CO2 Cooling unit monobloc

Refrigeration unit charged with CO2 (GWP=1) with inverter board to control to speed; Fast extraction due to the Slide in - Slide out system (patented)



Efficiency energy rating

TECHNICAL FEATURES

Dimensions and finishing

Number of trays standard/maximum	6/7
Number of selections	Up to 70
Hieght - Width - Depth	1830 - 1050 - 790 mm
Footprint with door open	1810 mm
Weight	340 Kg
Aesthetic finishing	Anodized grey and black

Electrical data

Power supply	230/50-60 V/Hz
Rated power	450 W
Minimal internal temperature	3°C with health control

Amenities

Protocols	Executive/MDB
Digital Display Trays	Optional
Anti-theft bars	Optional
Easy Click system	Yes
Photocells product delivery	Yes
Pre-cooling compartment	Yes
WI-FI and bluetooth LE native	Yes